

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ADT-LINK ANY
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ADT-LINK IS PROHIBITED

版本 REV	变更内容 DESCRIPTION	变更号 ECN No.	日期 DATA
1.0	ISSUE	REL	2025-Jan.-07

TOP VIEW

BOTTOM VIEW

3D VIEW

FEATURES:
PCIe X4 to M.2 NVMe Adapter
Specification: PCIe 5.0x4

PHYSICAL PROPERTIES:
Operation Temp.Range: -40°C to 80°C
Flammability rating: 94V-0

NOTE
1.100% OPEN/SHORT TEST.
2.DIMSION MARK "▼" BY QC CHECK.

No.	PART NO.	DESCRIPTION	Q'TY
5	Screw	M2 2280 screw	1Pcs
4	Shield	Solid, Full-height, Black Baffle	1Pcs
3	Base	FR4, 2mm PCB BASE	1Pcs
2	Connector	M.2 3.2H 67PIN 0.5mm Pitch, M key, SMT, Top-Mount , R/A H/F connector	1Pcs
1	Edge PCB	PCIe X4 CARD EDGE PCB , Black,ON GOLD FINGER, UL 94V-0	1Pcs



ADT-LINK

TITLE: PCIe X4 to M.2 NVMe Adapter		DWG NO.: ADT-R24A-001			
		CUSTOMER NO. : R24A-xxxxcm			
		CUSTOMER P/N: R24A			
	SCALE	UNIT	CUS REV.	ADT REV.	DATE
	NONE	mm	1.0	1.0	2025-Jan.-07
DRAWING/制图 Dane		CHECKED/审核		APPROVED/核准	